

## AXA Series

25 Watts

### Data Sheet

**Total Power:** 25 W  
**Input Voltage:** 24 or 48 V  
**# of Outputs:** Single and Dual

### SPECIAL FEATURES

- Package size 1.0" x 1.0" x 0.4"
- Ultra-wide 4:1 input range:  
9 - 36 V<sub>in</sub>, 18 - 75 V<sub>in</sub>
- Very high efficiency up to 90%
- Operating temperature range:  
-40 °C to +85 °C (with derating)
- Output voltage adjustable
- I/O isolation voltage 1500 Vdc
- Remote ON/OFF control
- Metal case with isolated baseplate
- CSA/UL/IEC/EN 60950-1 Safety Approval

### SAFETY

- cUL/UL 60950-1
- IEC/EN 60950-1



### Electrical Specifications

Input	
Input range	9 - 36 Vdc, 18 - 75 Vdc
Efficiency	90% @ 12 Vo
Output	
Voltage tolerance	±2.0%
Line regulation	±0.2%
Load regulation	±1.0%
Noise/ripple	150 mV
Overload protection	150% typ of I <sub>o</sub> max, hiccup
Short circuit protection	Hiccup mode
Switching frequency	285 KHz
Isolation	
I/O isolation	I/O: 1500 Vdc
Insulation resistance	1000 Mohm
Insulation capacitance	2000 pF



### Environmental Specifications

<b>Operating ambient temperature range</b>	-40 °C to +85 °C
<b>Storage temperature</b>	-50 °C to +125 °C
<b>Humidity</b>	5% to 95% non-condensing
<b>MTBF</b>	444 Khrs calculated

## Ordering Information

Part Number	Input Voltage	Output Voltage	Output Current	Efficiency	Max Out Cap	Power
AXA06F18-L	9 - 36 Vdc	3.3 V	6 A	87%	10300 $\mu$ F	19.8 W
AXA05A18-L	9 - 36 Vdc	5 V	5 A	89%	6800 $\mu$ F	25 W
AXA02B18-L	9 - 36 Vdc	12 V	2.09 A	89%	1200 $\mu$ F	25 W
AXA02C18-L	9 - 36 Vdc	15 V	1.67 A	90%	750 $\mu$ F	25 W
AXA01BB18-L	9 - 36 Vdc	$\pm$ 12 V	$\pm$ 1.04 A	89%	680 $\mu$ F	25 W
AXA01CC18-L	9 - 36 Vdc	$\pm$ 15 V	$\pm$ 0.84 A	89%	380 $\mu$ F	25 W
AXA06F36-L	18 - 75 Vdc	3.3 V	6 A	88%	10300 $\mu$ F	19.8 W
AXA05A36-L	18 - 75 Vdc	5 V	5 A	90%	6800 $\mu$ F	25 W
AXA02B36-L	18 - 75 Vdc	12 V	2.09 A	90%	1200 $\mu$ F	25 W
AXA02C36-L	18 - 75 Vdc	15 V	1.67 A	90%	750 $\mu$ F	25 W
AXA01BB36-L	18 - 75 Vdc	$\pm$ 12 V	$\pm$ 1.04 A	89%	680 $\mu$ F	25 W
AXA01CC36-L	18 - 75 Vdc	$\pm$ 15 V	$\pm$ 0.84 A	89%	380 $\mu$ F	25 W

## Mechanical Dimensions



Pin Connections		
Pin	Single Output	Dual Output
1	+Vin	+Vin
2	-Vin	-Vin
3	+Vout	+Vout
4	Trim	Common
5	-Vout	-Vout
6	Remote On/Off	Remote On/Off

- All dimensions in mm (inches)
- Tolerance: X.X $\pm$ 0.5 (X.XX $\pm$ 0.02)  
X.XX $\pm$ 0.25 (X.XXX $\pm$ 0.01)
- Pin diameter  $\varnothing$  1.0  $\pm$ 0.05 (0.04 $\pm$ 0.002)

## WORLDWIDE OFFICES

### Americas

2900 South Diablo Way  
Suite B100  
Tempe, AZ 85282, USA  
+1 888 412 7832

### Europe (UK)

Ground Floor Offices, Barberry House  
4 Harbour Buildings, Waterfront West  
Brierley Hill, West Midlands  
DY5 1LN, UK  
+44 (0) 1384 842 211

### Asia (HK)

14/F, Lu Plaza  
2 Wing Yip Street  
Kwun Tong, Kowloon  
Hong Kong  
+852 2176 3333

**ARTESYN**<sup>™</sup>  
An Advanced Energy Company

[www.artesyn.com](http://www.artesyn.com)

Artesyn Embedded Technologies, Artesyn Embedded Power, Artesyn, and all Artesyn related logos are trademarks and service marks of Artesyn Embedded Technologies, Inc. All other names and logos referred to are trade names, trademarks, or registered trademarks of their respective owners. Specifications are subject to change without notice. © 2019 Artesyn Embedded Technologies, Inc. All rights reserved. For full legal terms and conditions, please visit [www.artesyn.com/legal](http://www.artesyn.com/legal).

For more information: [www.artesyn.com](http://www.artesyn.com)  
For support: [productsupport.ep@artesyn.com](mailto:productsupport.ep@artesyn.com)